

ARCHITECTURAL

**GRATES + DRAINS** 

Code 125Custom-304-B

Category Custom Made

Recessed Channel

158mm L<u>h a a a a a a a a a a a a a a a a a a</u>

> U Channel 158mm

dimensions.

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on

Channel Material Stainless Steel

Grate Style CR

Steel Grade 304

Range Custom Fabrication



# 125Custom-304-B **Linear Drain**

304 stainless steel grate and channel up to 125mm wide and custom channel depth.

#### Depth between 27mm and 135mm for a U shape Channel

Available with a 5mm wire x 5mm gap, 5mm wire x 5mm gap or 5mm wire x 5mm gap GRATE GRIP slip resistant dimple finish.

Suits Load Class B.

For site specific needs or unusual situations, choose from our Custom

Stormtech can customise any drainage requirements to achieve

#### **SPECIFICATIONS + DIMENSIONS**

**Channel Width Channel Depth** Length(s) **Outlet Size** 

DN40, DN50, DN65, DN80, DN100

## STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

## **PRODUCT APPLICATIONS**

**Bathroom Drainage** Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage **Driveway Drainage** 

Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 14/08/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

Phone 1300 653 403 Email info@stormtech.com.au

Fabrication range.

# maximum efficiency.

135mm 27mm - 135mm As Required

40mm Minimum

150mm Maximum

27mm Minimum

45mm Maximum